

Прочный и компактный iSC Touch 250 - быстрое и надежное POS-решение для ритейла, экономящее рабочее пространство кассира.

Highest Security

Meets the industries highest and latest hardware and software security requirements and is PCI-PTS 3.x certified. Complies with SRED and open protocols modules. Supports the point-to-point encryption (P2PE) solutions available in the market, thus reducing PCI DSS scope.

All Payment Options

Equipped to handle all forms of payment including EMV Chip & PIN, Chip & Sign, MagStripe, Signature Capture, wand Contactless. Also supports new payment options such as NFC loyalty and couponing, wallets, and QR codes.

Electronic Signature

Offers high quality and durability signature capture capabilities for electronic payments, receipt storage and new business applications (such as contracts, warranty programs, enrollment). Authentication with biometric signature is available including speed and screen pressure for better recognition.

Designed for Retailers

Designed for use in some of the harshest multiline environments. The glass display is highly resistant to impacts and scratching, with a lifespan of 1,000,000 signatures. Its magnetic stripe reader includes two magnetic read heads to reduce read errors while the smart card reader was built to endure 500,000 card insertions. Single cable with a multipoint mono connector for easy integration & terminal replacement.

Fast Checkout

Optimized glass display to reduce reflectivity and assure good readability in dim environments. Large, ADA-friendly backlit keypad. Fast processor, for instant transactions execution.

Connectivity and Communication

Provides a full portfolio of connectivity: USB host/device, Ethernet, RS232, Tailgate. Field-upgradable WiFi, Bluetooth and GPRS. ComBox accessory increases the number of connectivity plugs to ease the solution's integration.

Large 4.3" 16/9 Capacitive Color Touchscreen

It's all about maximizing user experience. Its remarkable 4.3" 16/9 QVGA capacitive color touchscreen enhances application interactivity.

Real Multimedia

Equipped with a powerful hardware video decoder to play multimedia content from the standard ultra-compressed H264 codec with a speaker and a stereo out headset.

Telium 2 Advanced

Empowered to manage image libraries, touchscreen and multimedia.

Full Set of Retail Accessories

Tailored for easy integration (terminal stands, metal-reinforced Kensington® Security Slot).

Eco-Friendly Manufacturing

All our iSC Touch Series manufacturing facilities are ISO 14001 certified.



НАИМЕНОВАНИЕ		iSC Touch 250
Процессор	Основной процессор	Thunder (ARM9), 450 MIPS
	Криптопроцессор	Booster (ARM7), 50 MIPS
Память	Внутренняя	128 Мб Flash NAND, 64 Мб SDRAM
	Внешняя	µSD до 32 GB
Операционная система		Telium 2
SAM		2
Ридеры карт	Магнитная полоса	Triple track ISO 1, 2, 3 Система всенаправленных головок
	Смарт карты	EMV L1, 500,000 считываний
	Бесконтактные карты	Встроенный ридер
Дисплей	Размер	4.3" 480 x 272, widescreen (16:9)
	Цветность	65K цветов Каленое стекло, емкостной тачскрин
	Тачскрин	Пальцы/стилус
Стилус		Не механический
Функция захвата подписи		Ресурс 1 млн подписей на экране
Клавиатура	Рельефное нанесение	15 клавиш/вандалоустойчивость Белая подсветка
Аудио		Динамик + аудиовыход 3.5 мм jack Встроенный Зуммер
Видео		Все видеоформаты, загружаемые по SDK + H264 кодек
Связь	USB	USB2.0 - Device
	USB host	USB2.0 - Host
	Последовательный порт	RS232
	Ethernet	10/100 BT
	Tailgate	Заводская опция
Питание	Powered USB	12V USB power
	POE	Совместимо с 802.3AF (опция)
	SDL	RS485 + питание (опция)
	Внешний источник	Опционально 8V до 12V
Размеры	Д x Ш x В	168 x 140 x 43 мм
Вес		580 г
Условия эксплуатации	Рабочие температуры	+5°C до 40°C
	Температура хранения	-20° до 70°C
	Отн. влажность	85% RH (без конденсата)
Защитный козырек		Заводская опция
Безопасность PCI PIN		Сертификация PCI PTS 3.x & 4.x



www.ingenico.com

ВВ(115093 .36 .1 191015 .51 / (495/812) 363 31 13

ingenico
Smart terminals